



IHT PRODUCT COMPARISON

SPECIFICATIONS

Model	Axle Size (in)	3/4"	3/4" / 1"	1"	1"	1.18"
	Axle Torque (ft lb)	131-171	171-217	217-405	405	650
	Max Vehicle Wt. (lbs)	675	675-697	697-728	728	1850
	Tire Size (in)	18/20"	22"	23"	24"	26"
K46		X	*			
K57			X			
K62			X	*		
K66 (Ground Engaging)				X		
K71 (Ground Engaging)				X	X	
K92 (Ground Engaging)						X

* Possible, but depends on vehicle weight and duty cycle.

AVAILABLE OPTIONS

Model	Internal Reservoir Housing	External Reservoir Required	Charge Pump	Auxiliary Hydraulics	4WD Mechanical	4WD Hydro-static	Servicable Filter	Differential Lock	Auto Diff Lock	Rear PTO	Internal Wet Disk Brake
K46 Type I		X							X		X
K46 Type II	X								X		X
K57 Type I	X		X		X	X			X		X
K57 Type II	X		X	X	X	X	X		X		X
K62		X						X			X
K66 Type I		X	X		X	X		X			X
K66 Type II		X	X	X	X		X	X			X
K71 Type I		X	X		X	X		X			X
K71 Type II		X	X	X	X	X	X	X			X
K92	X		X	X	X	X	X	X		X	X

All units standard with flexible mounting and control operation.



P.P.H.U. Agma-tech
 ul. Siwka 34, 31-588 Kraków, tel. 012 346 13 96
 ul. Ks. Siemaszki 39, 31-207 Kraków, tel. 012 416 33 17
 e-mail: robin@agma-tech.krakow.pl
 www.agma-tech.pl